



# PRO PINK<sup>®</sup> COMFORTSEAL<sup>™</sup> SILL GASKET

Owens Corning<sup>®</sup> ProPink ComfortSeal<sup>™</sup> Sill Gasket is a polyethylene foam gasket, which provides resilient sealing in new and retrofit construction.

## Features

- Minimizes air leakage
- Resists moisture
- Insect resistant
- Installs quickly and easily, with no special tools
- Long-lasting and durable



## Physical properties

	PROPERTY	TEST METHOD	VALUE
PHYSICAL	Vertical compressive strength (psi)	ASTM D3575-08	
	Compressive strength	Suffix D @ 25%/50%	2.7/10.4
	Compression set (%)	ASTM D3575-08 Suffix B	29.4
	Tear resistance (lb/ft <sup>2</sup> )	ASTM D3575-08 Suffix T MD/CMD	8.3/11.5
	Density (lb/ft <sup>3</sup> )	ASTM D3575-08	1.2
MOISTURE	Water absorption (lb/ft <sup>2</sup> )	ASTM D3575-08 Suffix L	< 0,1 / sq ft / 24 hours
	Water vapor transmission rate GM/100 in <sup>2</sup> /24 hours	ASTM F-1249 Method 3005 FED STD 101	0.089
THERMAL	Thermal resistance R-Value @ initial thickness (hr-ft <sup>2</sup> -0F/BTU)	ASTM C518-91	0.68

1. R means resistance to heat flow; the higher the value, the greater the insulation power. Value given is for initial thickness. Value after installation/compression will be lower.

## Standards, code compliance

- Class A Fire Rating
- Does not support mold growth
- GreenGuard™ Certified

## Applications

- Provides a seal against air leakage, moisture, and insect intrusion at the juncture of the foundation wall and sill plate.
- Expansion joint material for poured concrete and concrete block slab and wall construction.

## Installation instructions

- Smooth the top surface of the foundation wall for minimal variation.
- Unroll the sill gasket on the top surface of the foundation wall or fasten to the bottom of the sill plate on tilt-up wall sections with ridged side toward roughest surface.
- Overlap all end and perpendicular joints.
- Pierce the sill gasket at anchor bolt locations.
- Set and anchor sill plate to the foundation wall.

Caution: ProPink ComfortSeal™ Sill Gasket is combustible and will ignite. The product may contain flammable vapors and should be stored in well-ventilated areas. Do not expose the product to open flame during shipping, storage, installation, or use.

## Recommended tools

- Safety glasses
- Cut-resistant gloves
- Ladder
- Construction or hammer stapler
- 5/16 inch heavy-duty staples
- Scissors or utility knife

## Dimensions

MATERIAL	COLOR	LENGTH	PRODUCT SIZE
Polyethylene Foam	Pink	50 ft rolls	3½", 5½", 7½" widths x 3/16" thick
Polyethylene Foam	Black	50 ft rolls	3½", 5½", 7½" widths x 3/16" thick

## Environmental and Sustainability

Owens Corning is a world leader in building material systems, insulation, and composite solutions, delivering a broad range of high-quality products and services.

Owens Corning is committed to driving sustainability by delivering solutions, transforming markets, and enhancing lives. More information can be found at [www.owenscorning.com](http://www.owenscorning.com).

## Certifications and sustainable features

- GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit [ul.com/gg](http://ul.com/gg)



## Disclaimer of liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein.



**OWENS CORNING INSULATING SYSTEMS, LLC**

ONE OWENS CORNING PARKWAY  
TOLEDO, OHIO, USA 43659

**1-800-GET-PINK®**  
[www.owenscorning.com](http://www.owenscorning.com)

Pub. No. 23514-J. Printed in U.S.A. May 2020.  
© 2020 Owens Corning. All Rights Reserved.